

P-LINK-4 (USB)

PC interface for power measurement. Four channels.



KEY FEATURES

READS ALL POWER DETECTORS TYPES

Thermopiles and photo detectors of the PH100 & PH20 series

MULTI-CHANNEL CAPABILITIES

Available with 1 or 4 channels

PC-BASED

Connects to your PC with included software

SMALL SIZE

Only 91 mm (L) x 57 mm (W) x 36 (H)

SERIAL COMMANDS

Serial commands are available on both versions to let you take full control

REAL-TIME STATISTICAL FUNCTIONS

Max, min, average, standard deviation, RMS and PTP stability, pulse # and repetition rate

USB, RS-232 OR ETHERNET

Choose your favourite communications port. The USB version is port-powered. Ethernet available only on 4-channel version.



SPECIFICATIONS

CONTROLLER AND GUI SPECIFICATIONS

Digital display size	Computer Screen
Data display	Real Time, Ratio, Line Plot, Histogram, Statistics and 3D Histogram
External trigger	None
Real-time data transfer	10 Hz
Serial commands via	USB

POWER METER SPECIFICATIONS

Power range (thermopile)	3 μ W - 30 kW
Power range (photodetector)	1 pW - 3 W
Device accuracy	± 0.5 % full scale
Statistics	Current value, max, min, average, standard deviation, RMS & PTP stability, time
Response time	1 sec

ENERGY METER SPECIFICATIONS

PHYSICAL CHARACTERISTICS

Dimensions	286W x 233H x 43D mm
Weight	2.5 kg

ORDERING INFORMATION

P-LINK-4 (USB)	202223
----------------	--------

INTERESTED IN THIS PRODUCT?

[GET A QUOTE](#)

Find your local sales representative at gentec-eo.com/contact-us